



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
AC2SX, 90° Elbow	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249-304/304L, 316L	200	165	ASME B31.3, ASME BPE
	3"		200	150	
	4"		200	125	
	6", 8"		150	75	
AC2F14, 90° Sweep Elbow	1 1/2", 2", 2 1/2"	A249-304/304L, 316L	200	165	
	3"		200	150	
	4"		200	125	
AC2F15, 90° Sweep Elbow	1", 1 1/2", 2", 2 1/2"	A249-304/304L, 316L	200	165	
	3"		200	150	
	4"		200	125	
AC2KSX, 45° Elbow	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249-304/304L, 316L	200	165	
	3"		200	150	
	4"		200	125	
	6", 8"		150	75	
AC2C31, 90° Reducing Elbow Non-Tapered	2" x 1", 2" x 1 1/2", 2 1/2" x 1 1/2", 2 1/2" x 2"	A249-304/304L, 316L	200	165	
	3" x 1 1/2", 3" x 2", 3" x 2 1/2"		200	150	
	4" x 2 1/2", 4" x 3"		200	125	




Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
AC7, TEE	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249-304/304L, 316L	200	165	
	3"		200	150	
	4"		200	125	
	6", 8"		150	75	
AC7R, Reducing Tee	3/4" x 1/2", 1" x 1/2", 1" x 3/4", 1 1/2" x 1/2", 1 1/2" x 3/4", 1 1/2" x 1", 2" x 1", 2" x 1 1/2", 2 1/2" x 2",	A249-304/304L, 316L	200	165	
	3" x 1 1/2", 3" x 2", 3" x 2 1/2"		200	150	
	4" x 2", 4" x 2 1/2", 4" x 3"		200	125	
	6" x 3", 6" x 4"		150	75	
AC9, Cross	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249-304/304L, 316L	200	165	
	3"		200	150	
	4"		200	125	
AC13HH, Heavy Duty Clamp	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A351 CF8	200	165	
	3"		200	150	
	4"		200	125	
	6", 8"		150	75	
AC13HP, High Pressure Clamp	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A351 CF8	350	350	
	3", 4"		245	245	
	6", 8"		175	175	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
AC14A, Butt-Weld Ferrule	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	5", 6", 8", 10"		150	75	
AC14H, Heavy Butt-Weld Ferrule	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6", 8"		150	75	
AC14X, Short-Weld Ferrule	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4", 5"		200	125	
	6", 8", 10", 12"		150	75	
AC14WL, Light Tank Welding Spud	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6", 8"		150	75	
AC14R, Recessless Ferrule	1", 1 1/2", 2", 2 1/2"	A 479 304/304L, 316L	200	165	
	3"		200	150	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	4"	A479 304/L316L	200	125	
AC14AHR, Rubber Hose Adapter	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		200	75	
AC14AHT, Tygon Hose Adapter	1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
AV14H, Tri-Clamp X Schedule 10 Butt weld	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
AC16, Solid End Cap	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4", 5"		200	125	
	6", 8", 10", 12"		150	75	
AC1714, Instrument Gauge Adapter	1" x 3/4", 1 1/2" x 1", 2" x 1", 2 1/2" x 2",	A 479 304/304L, A479 316L	200	165	
	3" x 2"		200	150	
	4" x 3"		200	125	
AC17F, Tri-Clamp X	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A 479	200	165	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
Flange Adapter	3"	304/304L, A479 316L	200	150	
	4"		200	125	
	6"		150	75	
AC21, Adapter (male) AC22, Adapter (female)	1/2" x 1/2", 1/2" x 3/4", 3/4" x 1/2", 3/4" x 3/4", 1" x 1", 1 1/2" x 3/4", 1 1/2" x 1", 1 1/2" x 1 1/4", 1 1/2" x 1 1/2", 1 1/2" x 2", 2" x 1 1/2", 2" x 2", 2 1/2" x 2", 2 1/2" x 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3" x 3"		200	150	
	4" x 4"		200	125	
AC23, Thermometer Cap	1", 1 1/2", 2", 2 1/2"	A 479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
AC28WA, Lateral	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
AC28B, True Y	1", 1 1/2", 2", 2 1/2"	A249 304/304L,	200	165	
	3"		200	150	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	4"	A249 316L	200	125	
	6"		150	75	
AC31, Concentric Reducer AC32, Eccentric Reducer	3/4" x 1/2", 1" x 1/2", 1" x 3/4" 1 1/2" x 1/2", 1 1/2" x 3/4" 1 1/2" x 1", 2" x 1", 2" x 1 1/2" 2 1/2" x 1 1/2", 2 1/2" x 2"	A249 304/304L, A249 316L	200	165	
	3" x 1 1/2", 3" x 2", 3" x 2 1/2"		200	150	
	4" x 2", 4" x 2 1/2", 4" x 3"		200	125	
	6" x 3", 6" x 4"		150	75	
	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"		200	165	
A2S, 90° Tube Bend	3"	A249 304/304L, A249 316L	200	150	
	4"		200	125	
	6"		150	75	
	1", 1 1/2", 2", 2 1/2"		200	165	
A2C, 90° Sweep Elbow	3"	A249 304/304L, A249 316L	200	150	
	4"		200	125	
	1", 1 1/2", 2", 2 1/2"		200	165	
AC2C 90° Sweep Elbow	3"	A249 304/304L, A249 316L	200	150	
	4"		200	125	
	1", 1 1/2", 2", 2 1/2"		200	165	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
A2F 90° Sweep Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
A2KS 45° Tube Bend	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A2K 45° Sweep Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
AC2KC 45° Sweep Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
A28WA Lateral	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A28B True Y	1", 1 1/2", 2", 2 1/2"	A249 304/304L,	200	165	
	3"		200	150	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	4"	A249 316L	200	125	
	6"		150	75	
A7W Tee	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A7WR Reducing Tee	3/4 x 1/2, 1 x 1/2, 1 x 3/4, 1 1/2 x 1/2, 1 1/2 x 3/4, 1 1/2 x 1, 2 x 1/2, 2 x 3/4, 2 x 1, 2 x 1 1/2, 2 1/2 x 1, 2 1/2 x 1 1/2, 2 1/2 x 2	A249 304/304L, A249 316L	200	165	
	3 x 1 1/2, 3 x 2, 3 x 2 1/2		200	150	
	4 x 2, 4 x 2 1/2, 4 x 3		200	125	
	6 x 3, 6 x 4		150	75	
A31W Concentric Reducer A32W Eccentric Reducer	3/4 x 1/2, 1 x 1/2, 1 x 3/4, 1 1/2 x 1/2, 1 1/2 x 3/4, 1 1/2 x 1, 2 x 1, 2 x 1 1/2, 2 1/2 x 1 1/2, 2 1/2 x 2	A249 304/304L, A249 316L	200	165	
	3 x 1 1/2, 3 x 2, 3 x 2 1/2		200	150	
	4 x 1 1/2, 4 x 2, 4 x 2 1/2, 4 x 3		200	125	
	6 x 2, 6 x 3, 6 x 4, 8 x 6		150	75	
2C 90° Sweep Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L,	200	165	
	3"		200	150	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	4"	A249 316L	200	125	
2F 90° Sweep Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
2E 90° Sweep Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
2K 45° Sweep Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
2P 45° Sweep Ell	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
7 Tee	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
13H Hex Union Nut	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
14A Plain Tube Ferrule	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
14AHR Rubber Hose Adapter	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
14AHT Tygon Hose Adapter	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
14WF Plain Short Weld Ferrule	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
14H Plain Heavy Tank Spud	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
14WL Plain Light Tank Spud	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
15A Threaded Tube Ferrule	1", 1 1/2", 2", 2 1/2"	A249	200	165	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	3"	304/304L, A249 316L	200	150	
	4"		200	125	
15AHR Rubber Hose Adapter	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
15AHT Tygon Hose Adapter	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
15WF Threaded Short Weld Ferrule	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
15H Threaded Heavy Tank Spud	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
15WL Threaded Light Tank Spud	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
16A Plain End Cap	1", 1 1/2", 2", 2 1/2"	A479 304/304L,	200	165	
	3"		200	150	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	4"	A479 316L	200	125	
31TP Concentric Taper Reducer 32TP Eccentric Taper Reducer	11/2 x 1, 2 x 1, 2 x 11/2, 21/2 x 11/2, 21/2 x 2	A479 304/304L, A479 316L	200	165	
	3 x 11/2, 3 x 2, 3 x 21/2		200	150	
	4 x 21/2, 4 x 3		200	125	
31TT Concentric Taper Reducer 32TT Eccentric Taper Reducer	11/2 x 1, 2 x 1, 2 x 11/2, 21/2 x 11/2, 21/2 x 2	A479 304/304L, A479 316L	200	165	
	3 x 11/2, 3 x 2, 3 x 21/2		200	150	
	4 x 21/2, 4 x 3		200	125	
A2ST 90° Tube Bend	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A2KST 45° Tube Bend	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A7WT TEE	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	6"		150	75	
A7WRT Reducing Tee with Extensions	3/4" x 1/2", 1" x 1/2", 1" x 3/4" 1 1/2" x 1/2", 1 1/2" x 3/4" 1 1/2" x 1", 2" x 1", 2" x 1 1/2" 2 1/2" x 1 1/2", 2 1/2" x 2"	A479 304/304L, A479 316L	200	165	
	3" x 1 1/2", 3" x 2", 3" x 2 1/2"		200	150	
	4" x 2", 4" x 2 1/2", 4" x 3"		200	125	
	6" x 3", 6" x 4"		150	75	
A9WT Cross	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
AC14T Long Butt-Weld Ferrule	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A31WT Concentric Reducer	3/4" x 1/2", 1" x 1/2", 1" x 3/4" 1 1/2" x 1/2", 1 1/2" x 3/4" 1 1/2" x 1", 2" x 1", 2" x 1 1/2"	A479 304/304L, A479 316L	200	165	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	2 1/2" x 1 1/2", 2 1/2" x 2"				
	3" x 1 1/2", 3" x 2", 3" x 2 1/2"		200	150	
	4" x 2", 4" x 2 1/2", 4" x 3"		200	125	
	6" x 3", 6" x 4"		150	75	
A2SX 90° Elbow	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6", 8"		150	75	
A2KSX 45° Elbow	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6", 8"		150	75	
A2WU 180° Return Bend	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A7W TEE	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	6"		150	75	
A7WR Reducing Tee	3/4" x 1/2", 1" x 1/2", 1" x 3/4"	A479 304/304L, A479 316L	200	165	
	1 1/2" x 1/2", 1 1/2" x 3/4"				
	1 1/2" x 1", 2" x 1", 2" x 1 1/2"				
	2 1/2" x 1 1/2", 2 1/2" x 2"				
	3" x 1 1/2", 3" x 2", 3" x 2 1/2"				
	4" x 2", 4" x 2 1/2", 4" x 3"		200	125	
	6" x 3", 6" x 4"		150	75	
A9W Cross	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A14VB Stub End (Type "A")	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249/A240 304/304L, A249/A240 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A16W CAP	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	6"		150	75	
A14HL Tube OD Buttweld X Sch 10	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
A19W Adapter	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A312 304/304L, A312 316L	200	165	
	3"		200	150	
	4"		200	125	
A22W Adapter	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
A28WA Lateral	1/2", 3/4", 1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
A31W Concentric Reducer A32W Eccentric Reducer	3/4" x 1/2", 1" x 1/2", 1" x 3/4" 1 1/2" x 1/2", 1 1/2" x 3/4" 1 1/2" x 1", 2" x 1", 2" x 1 1/2" 2 1/2" x 1 1/2", 2 1/2" x 2" 3" x 1 1/2", 3" x 2", 3" x 2 1/2"	A249 304/304L, A249 316L	200	165	
			200	150	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	4" x 2", 4" x 2 1/2", 4" x 3"		200	125	
	6" x 3", 6" x 4"		150	75	
AY13IS Clamp	1", 1 1/2", 2", 2 1/2"	A351 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
AY14AHR Rubber Hose Adapter	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
AY14AHT Tygon Hose Adapter	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
AY14WI Short Weld Ferrule	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
AY14WLI Long Weld Ferrule	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
AY15AHR Rubber Hose Adapter	1", 1 1/2", 2", 2 1/2"	A479	200	165	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	3"	304/304L, A479 316L	200	150	
	4"		200	125	
AY15AHT Tygon Hose Adapter	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
AY15WI SHORT WELD FERRULE	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
AY15WLI LONG WELD FERRULE	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
AY16AI14I CAP AY16AI15I CAP	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
AV2SX 90° Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
AV2KSX 45° Elbow	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
AV7 TEE	1", 1 1/2", 2", 2 1/2"	A249 304/304L, A249 316L	200	165	
	3"		200	150	
	4"		200	125	
AV13HH Heavy Duty Clamp (Single Pin)	1", 1 1/2", 2", 2 1/2"	A351 CF8	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
AV14WL Light Butt-Weld Ferrule	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6"		150	75	
AV14X Short Welding Ferrule	1", 1 1/2", 2", 2 1/2"	A479 304/304L, A479 316L	200	165	
	3"		200	150	
	4"		200	125	
	6", 8", 10"		150	75	
AV16 Solid End Cap	1", 1 1/2", 2", 2 1/2"	A479	200	165	



Fittings	Size	Constructed Material	MAWP (psi)		Codes of Construction
			Ambient 100 °F [38 °C]	Design Temp. 250 °F [121 °C]	
	3"	304/304L, A479 316L	200	150	
	4"		200	125	
	6"		150	75	
AV31 Concentric Reducer	1 1/2 x 1, 2 x 1, 2 x 1 1/2, 2 1/2 x 1 1/2, 2 1/2 x 2	A479 304/304L, A479 316L	200	165	
	3 x 2, 3 x 2 1/2		200	150	
	4 x 2 1/2, 4 x 3		200	125	